



JCHI

AERIAL WORK PLATFORMS

Compact Scissor lifts

	GTJZ-0408A	GTJZ-0508A
最大工作高度 Max. working height(m)	5.4	6.8
最大平台高度 Max. platform height(m)	3.6	5
收藏高度 Stowed height(m)	2.01	2.02
防护栏高度 Guardrail height(m)	0.95	0.95
收藏长度 Length(m)	1.45	1.45
收藏宽度 Width(m)	0.88	0.88
平台尺寸 Platform dimensions(L*W) (m)	1.45x0.88	1.45x0.88
额定载荷 Lifting capacity (kg)	250	250
轴距 Axle base(m)	1.11	1.11
内部转弯半径 Inside turning radius(m)	0.64	0.64
外部转弯半径 Outside turning radius(m)	2.65	2.65
离地间隙 Ground clearance(m)	0.06	0.06
深坑保护装置展开离地间隙 Pothole guard clearance(m)	0.02	0.02
重量请参阅(机器重量根据选件配置不同而有所差异) Machine weight (differs in options)(Kg)	850	900
爬坡能力 Gradeability(%)	20	20
电源 Power		
平台控制电压 Control pressure(V)	24	24
平台充电电压 Charging pressure(V)	~220	~220
液压系统压力 Hydraulic pressure(MPa)	20	20
轮胎尺寸 Tire(D*W) (m)	0.3x0.1	0.3x0.1
液压系统容量 Hydraulic capacity(L)	15	15
行驶速度 Traveling speed(m/s)		
平台收起时最大值 Platform stowed	0.75	0.75
平台升起时最大值 Platform raised	0.15	0.15
蓄电池组 Battery	进口Imported— T105/4-6V-209AH	进口Imported— T105/4-6V-209AH



QTJZ-10

QLYS8

QT8Z-25

QTBV-220

QTJZ-10

QT8Z-30

QT8Z-35



Beijing Jingcheng Heavy Industry Co. Ltd.

2, Chuangyeyuan Road,
Xinghu Industrial Garden, Taihu Town,
Tongzhou District, 101116, Beijing,
P. R. China
Tel: 86 10-6153 9210
www.jchic.com
sales@jchic.com



*Contact us for configuration details and performance.
JCHI reserves the right to modify specifications without prior notification.